

WATCH
THE WORLD
UNFOLD





UNIFOLD^{HI}

INSTALL EFFORTLESSLY WITH THE UNIFOLD HI

Meet the UNIFOLD HI, our new Bifold door with 110mm glass-to-glass sight-lines, pre-gasketed snap-in glazing beads for effortless installation, options for PAS24 Certification and U values from as low as 0.8 W/m2K

SLIM 110MM GLASS TO GLASS SIGHTLINES

MODERN SQUARE LOOK

COLOUR-MATCHED HARDWARE

FULLY OPENABLE CORNERS

DOUBLE OR TRIPLE GLAZING

PAS24 CERTIFIED OPTIONS

MULTI-POINT LOCKING

BFRC RATING A++ TRIPLE GLAZED*

ADJUSTABLE JAMB OPTION

U VALUE FROM 0.8 W/M2K



Maximum Panel Width	1200 mm
Maximum Panel Height	3000 mm
Maximum Panel Weight	120 kg

FRAME DEPTH	80 mm
GLAZING THICKNESS	25-48 mm
GLAZING METHOD	Internally Beaded
GLAZING	Double or Triple
FINISHES	Single or Dual. All RAL Colours

ENHANCED SECURITY	
PAS24	Yes
MULTI-POINT LOCKING	Yes

PERFORMANCE	
U-VALUE	From 0.8 W/m2K
AIR PERMEABILITY	Class 4
WATER TIGHTNESS	Class E750
WIND RESISTANCE	Class C3

THRESHOLD HEIGHT	
STANDARD	46.5 mm
LOW	28.5 mm

*on request